



JD47 NON-THERMAL DOOR AND SHOPFRONT

Flexible aluminium shopfront and door system for commercial applications.

JD47 is a non-thermal aluminium door and shopfront system designed for a wide range of commercial applications where flexibility, durability and ease of fabrication are key.

Well suited to retail, leisure and internal partitioning environments, the system provides a practical aluminium solution for projects where thermal performance is not required.

Applications

Retail Premises • Offices • Schools • Leisure Facilities •
Car Showrooms • Commercial Buildings

Key Benefits


- Flexible system supporting a wide range of shopfront designs
- Slim 50mm sightlines for clean commercial aesthetics
- Designed for efficient fabrication and installation
- Proven system for internal and external commercial applications
- Integrated doors, screens and partitioning options



50mm
Sightlines



Non-Thermal
System



Range of
Configurations



Cut to Length
Service



Fast Reliable
Service

One systems house.

Multiple accredited solutions.



JD47 is used across retail, leisure and public sector projects, offering a practical solution for both internal and external applications where thermal performance is not a requirement.

With a wide range of configurations available, including single and double doors, automatic entrances and glazed screens, JD47 supports consistent shopfront design across a variety of building types.

Key Features

- Integral external beading for improved security
- 50mm sightlines across doors and screens
- Wide range of thresholds and header bar options to support swing doors and sliding doors
- Punch tool preparation available
- Compatible with single and double glazing
- Suitable for internal and external applications

Hardware and Configuration

- Single and double hinged and sliding doors
- Manual locking hardware options
- Panic exit hardware options
- Access control remote access options
- Can be integrated with TD68 Thermal Commercial Doors, TW70 TruEnergy Windows and JCW Curtain Walling

Performance and Specification

- Frame depth: 47mm
- Glazing range: 6-28mm
- Optimal double glazing: 24mm

Sizes

- Single: 1300mm (W) × 3000mm (H)
- Double: 2500mm (W) × 3000mm (H)

Speak to our team about system performance, specification and Secured by Design compliance.



Unit C, 186 Torrington Avenue,
Coventry CV4 9AJ



sales@jackaluminium.co.uk
www.jackaluminium.co.uk



024 7646 7449
Mon - Fri 9am-5pm